



TECHNICAL SPECIFICATION

	SL500/FL LED	SL500 LED	SL700 LED	SL500/700 LED	SL700/700 LED
Optical and mechanical					
Diameter (mm)	500	500	700	500/700	700/700
Illumination (Lx)	40000 - 90000	40000 - 90000	6000 - 160000	40000 – 90000 / 60000 - 160000	60000- 160000
Color Temperature (k)	3500-5000	3500-5000	3500-5000	3500-5000	3500-5000
Color Rendering Index (CRI) (Ra)	85-98	85-98	85-98	85-98	85-98
Color Rendering Index (CRI) R9	>90	>90	>90	>90	>90
Ratio of radiation illumination (mW/M ² – lux)	< 3.6	< 3.6	< 3.6	< 3.6	< 3.6
Heat dissipation (mW/M ² – lux)	< 3.8	< 3.8	< 3.8	< 3.8	< 3.8
Irradiation w/ m ²	232	232	539	232/539	539
Diameter of Light Spot (mm)	120-350	120-350	120-350	120-350	120-350
Focal Length (mm)	> 650	> 650	> 650	> 650	> 650
Lighting Depth (mm)	700-1500	700-1500	700-1500	700-1500	700-1500
Cavity penetration (%)	95	95	95	95	95
Shadowless Rate (%)	78	78	98	78/98	98
LED Working Life (h)	50,000	50,000	50,000	50,000	50,000
Electrical					
Input Voltage (V)	120/220	120/220	120/220	120/220	120/220
Frequency (Hz)	60/50	60/50	60/50	60/50	60/50
Power (W)	55	55	120	55/120	120
LED Panels	6	6	6	6	6
LED per panel	9 LED	9 LED	18 LED	18 LED	18 LED
Battery Backup	2-3 hours	Optional, 2-3 hours	Optional, 2-3 hours	Optional, 2-3 hours	Optional, 2-3 hours
Camera (Optional)					
Effective Pixels (horizontal X vertical)	440,000 (752x585)				
Shutter	1/50 ~ 1/10, 000s				
Exposure	Auto, Backlight compensation				
Balance	Auto White Balance				
Gain Control	Auto, EV compensation, Dynaview				
Lens Type	Zoom				
Compression Format	JPEG, MPEG-4, H.264				
Agreement	TCP/IP, HTTP, ARP, ICMP, FTP, SMTP, DHCP, SNMP, DNS, NTP, RTP/RTCP				
Horizontal Resolution	480 TV lines				
SNR	=50dB				
Camera rotation	330°				

Contáctenos para información adicional
 Nota: Especificaciones sujetas a cambios sin previo aviso.



6800 N.W. 77 Court, Miami, FL 33166
 Phone: 305-477-6331 • Fax: 305-477-5351
 sales@advanced-inst.com
www.advanced-inst.com